

Series 35-45

HOW TO ORDER



| BODY TYPE | PORT SIZE | VALVE FUNCTION/MANIFOLD TYPE |
|---|-----------------------------------|-----------------------------------|
| Inline | O Manifold Body Only | O Manifold Body Only |
| A Individual Inline | B #10-32 UNF (Inline Only) | B 3 way N.C. Only (Inline) |
| D Indiv. Inline w/2 Manifold Mount Ports | D M5 (Inline Only) | |

Note : there is no manifold base for the 35 series.
The manifold valve can only mount to a circuit bar, see note below

Manifold

- E** Manifold Body (N.C. Only Poppet)
- G** Manifold Body w/Gage Port (N.C. Only Poppet)




| BODY TYPE | PORT SIZE | VALVE FUNCTION/MANIFOLD TYPE |
|---|----------------------------------|--|
| Inline | O Manifold Body Only | Inline |
| A 4 Port Body | A 1/8" NPT | 1 No Flow Controls |
| B 5 Port Body | B #10-32 UNF | Bases - Regulators |
| D 4 Port Body "O" Ring Mount -All Bottom Ports | C 1/8" BSPPL | O Valve Only - No Base |
| E 5 Port Body "O" Ring Mount -3 Bottom Ports Inlet and Cylinders | D M5 (Metric) | A Individual Base |
| F 4 Port Body "O" Ring Mount-Bottom Cylinder Ports Only | F #10-32 UNF Bottom Ports | C Manifold Base |
| | G M5 Bottom Ports | E Manifold w/Regulator w/Slotted Stem |
| | H "O" Ring Mount Ports | G Manifold w/Regulator w/Locking Slotted Stem |
| | J 1/8" NPT Bottom Ports | J Manifold w/Regulator w/Locking Knob |
| | K 1/8" BSPPL Bottom Ports | |

Base Mount

- O** For Base Only - No Valve
- L** Base Mount Body
- M** Base Mount Body with Gage Port

MANIFOLD MOUNT ACCESSORIES

- M-45008-01** End Plate Kit
- 16455** Pressure Seal Between Manifold
- 19753** Tie Rod
- N-45008** Isolator Kit - Inlet and Exhaust
- N-45009** Isolator Kit - Inlet only
- N-45010** Isolator Kit - Exhaust only
- N-45015** End Cover Plate - Plain
- N-45016** End Cover Plate w/Flow Controls
- N-45017** Flow Control Needle Assembly



| VOLTAGE | LEAD LENGTH | MANUAL OPERATOR | ELECTRICAL CONNECTION |
|-------------------------|--------------------|-------------------------------|--|
| FR 12VDC (0.6 W) | A 18" Leads | 0 No operator | BA Grommet |
| FS 24VDC (0.6 W) | B 24" Leads | 1 Non-locking Recessed | CA Conduit 1/2" NPS† |
| FV 12VDC (0.4 W) | C 36" Leads | 2 Locking Recessed | CM Metal Conduit 1/2" NPS† |
| | D 48" Leads | 3 Non-locking Extended | CN Metal Conduit w/grd. 1/2" NPS† |
| | E 72" Leads | 4 Locking Extended | External Plug-in |
| | J* 6" Leads | | FM Plug-in (For ECD & ECE Bar) |
| | | | JB Rectangular Plug-in† |
| | | | JM Rectangular Male only† |
| | | | KA Mini Plug-in |
| | | | KJ Mini Plug-in Male only |
| | | | TA Dual Tabs (.110) Plain |
| | | | TJ Dual Tabs (.110) Plain |

*Use "J" for external plug-in connectors

NOTE : For valves mounted to a circuit bar reference MAC circuit bar Catalog for ordering info.
For the 35 series circuit bar, use MOD FM01 after circuit bar part number.

† Available on individual valves and circuit bars.