



R e m o t e a i r v a l v e s

Function	Port size	Flow (Max)	Individual mounting	Series
3/2 NO-NC, 2/2 NO-NC	2" - 2 1/2"	65.0 C_v	Inline	


OPERATIONAL BENEFITS

1. Balanced spool, immune to variations of pressure.
2. Short stroke with high flow.
3. The piston (booster) provides maximum shifting forces.
4. Powerful return thanks to the combination of mechanical and air springs.
5. Bonded spool with minimum friction, shifting in a glass-like finished bore.
6. Wiping effect eliminates sticking.
7. Low leakage rate.



1100
55
56
57
58
59

HOW TO ORDER

Port size	Air spring	NC valve
2" NPTF	Internal	
2 1/2" NPTF		59B-52-RA
2" NPTF	External	59B-53-RA
2 1/2" NPTF		59B-52-RE
		59B-53-RE

700
900
82

Air pilot port : 1/8" NPTF.

Note: Designation "RE" required on remote air pilot models with main valve pressures of vacuum to 25 PSI. "RE" provides an external pilot port and should have a pressure range of 25-75 PSI. Since the external pilot supplies the air spring, it must not exceed the remote air pilot signal pressure.

6300
6500
6600
2700
1800
ISO 1
ISO 2
ISO 3

TECHNICAL DATA

Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 150 PSI
Air signal pressure :	25 - 150 PSI \geq main valve pressure
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F to 210°F)
Filtration :	40 μ
Temperature range :	0°F to 120°F (-18°C to 50°C)
Flow (at 6 bar, $\Delta P=1bar$) :	2" : (60.0 C _v), 2 1/2" : (65.0 C _v)

- Spare parts : • Remote air pilot block : R-59003. • Check valve : 70019.
- Options : • BSPP threads.

DIMENSIONS

Dimensions shown are metric (mm)

Ø 13,5 MT'G HOLES

